## **CLAIMS**

5

7

8

9

10

11

12

13

14 15

16

17

18

19

20

21

23

24 25 1. A multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection determiner configured to determine a source selected for a Mopy in a Mopy job, wherein the source for the Mopy may be selected from multiple sources on the MFD;

a destination-selection determiner configured to determine a destination selected for a Mopy in a Mopy job wherein the destination for the Mopy may be selected from multiple destinations on the MFD;

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to a MFD.

## 2. A MFD comprising:

a printing engine;

multiple sources;

multiple destinations;

a receiver configured to receive a Mopy job from a Mopying control system as recited in claim 1.

**3.** A printer driver comprising a Mopying control system as recited in claim 1.

3

6

7

9

10

11

12

13 14

15

16

17

18

19 20

21

22

23 24 25

An application comprising a Mopying control system as recited in 4. claim 1. An operating system comprising a Mopying control system as 5. recited in claim 1. A method facilitating multiple-original-output ("Mopying") control of a Mopy-enabled multifunction device (MFD), the method comprising:

specifying a source for a Mopy in a Mopy job, wherein the source for the Mopy may be one of multiple sources on the MFD;

specifying a destination for a Mopy in a Mopy job wherein the destination for the Mopy may be one of multiple destinations on the MFD.

A method as recited in claim 6, further comprising: 7.

formatting a Mopy job, such job includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

transmitting the Mopy job to a MFD.

computer-readable medium having computer-executable 8. Α instructions that, when executed by a computer, performs the method as recited in claim 6.

3

5

6

7

9

10

11

12

13

14 15

16

17

18

19

20

21

23

24 25 **9.** A multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection specifier configured to select a source for each Mopy in a Mopy job, wherein a source for the Mopy may be selected from multiple sources on the MFD;

a destination-selection specifier configured to select a destination for each Mopy in a Mopy job, wherein a destination for the Mopy may be selected from multiple destination on the MFD.

## 10. A system as recited claim 9, further comprising:

- a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for each Mopy in the job and destination-selecting directions for each Mopy in the job;
  - a Mopy-job transmitter configured to transmit the Mopy job to a MFD.

## 11. A MFD comprising:

a printing engine;

multiple sources;

multiple destinations;

- a receiver configured to receive a Mopy job from a Mopying control system as recited in claim 9.
- **12.** A printer driver comprising a Mopying control system as recited in claim 9.

An application comprising a Mopying control system as recited 13. in claim 9 An operating system comprising a Mopying control system as 14. recited in claim 9.